

Supplementary Specification to API Standard 674 Reciprocating Positive Displacement Pumps

Revision history

VERSION	DATE	PURPOSE
1.0	May 2021	Issued for Use

Acknowledgements

This IOGP Specification was prepared by a Joint Industry Programme 33 Standardization of Equipment Specifications for Procurement organized by IOGP with support by the World Economic Forum (WEF).

Disclaimer

Whilst every effort has been made to ensure the accuracy of the information contained in this publication, neither IOGP nor any of its Members past present or future warrants its accuracy or will, regardless of its or their negligence, assume liability for any foreseeable or unforeseeable use made thereof, which liability is hereby excluded. Consequently, such use is at the recipient's own risk on the basis that any use by the recipient constitutes agreement to the terms of this disclaimer. The recipient is obliged to inform any subsequent recipient of such terms.

Please note that this publication is provided for informational purposes and adoption of any of its recommendations is at the discretion of the user. Except as explicitly stated otherwise, this publication must not be considered as a substitute for government policies or decisions or reference to the relevant legislation relating to information contained in it.

Where the publication contains a statement that it is to be used as an industry standard, IOGP and its Members past, present, and future expressly disclaim all liability in respect of all claims, losses or damages arising from the use or application of the information contained in this publication in any industrial application.

Any reference to third party names is for appropriate acknowledgement of their ownership and does not constitute a sponsorship or endorsement.

Copyright notice

The contents of these pages are © International Association of Oil & Gas Producers. Permission is given to reproduce this report in whole or in part provided (i) that the copyright of IOGP and (ii) the sources are acknowledged. All other rights are reserved. Any other use requires the prior written permission of IOGP.

These Terms and Conditions shall be governed by and construed in accordance with the laws of England and Wales. Disputes arising here from shall be exclusively subject to the jurisdiction of the courts of England and Wales.

Foreword

This specification was prepared under Joint Industry Programme 33 (JIP33) "Standardization of Equipment Specifications for Procurement" organized by the International Oil & Gas Producers Association (IOGP) with the support from the World Economic Forum (WEF). Companies from the IOGP membership participated in developing this specification to leverage and improve industry level standardization globally in the oil and gas sector. The work has developed a minimized set of supplementary requirements for procurement, with life cycle cost in mind, resulting in a common and jointly agreed specification, building on recognized industry and international standards.

Recent trends in oil and gas projects have demonstrated substantial budget and schedule overruns. The Oil and Gas Community within the World Economic Forum (WEF) has implemented a Capital Project Complexity (CPC) initiative which seeks to drive a structural reduction in upstream project costs with a focus on industry-wide, non-competitive collaboration and standardization. The CPC vision is to standardize specifications for global procurement for equipment and packages. JIP33 provides the oil and gas sector with the opportunity to move from internally to externally focused standardization initiatives and provide step change benefits in the sector's capital projects performance.

This specification has been developed in consultation with a broad user and supplier base to realize benefits from standardization and achieve significant project and schedule cost reductions.

The JIP33 work groups performed their activities in accordance with IOGP's Competition Law Guidelines (November 2020).

Table of Contents

	Foreword	1
	Introduction	3
2	Normative References	5
4	General	5
	4.1 Units of Measurement	5
	4.2 Subvendor control	5
6	Basic Design	5
	6.1 General	5
	6.5 Cylinder Connections	6
	6.7 Liquid End Features	6
	6.8 Power End Running Gear	6
	6.9 Direct-Acting Pump	7
	6.11 Materials	7
	6.12 Nameplates and Rotation Arrows	7
7	Accessories	8
	7.1 Drivers	8
	7.5 Controls and Instrumentation	8
	7.6 Auxiliary Piping	8
	7.7 Pulsation and Vibration Control Requirements	8
8	Inspection, Testing, and Preparation for Shipment	9
	8.1 General	9
	8.3 Testing	9
	8.4 Preparation for Shipment	9

Introduction

The purpose of this specification is to define a minimum common set of requirements for the procurement of reciprocating positive displacement pumps in accordance with API Standard 674 Positive Displacement Pumps—Reciprocating, Third Edition, December 2010, including Errata 2, April 2015, reaffirmed November 2016 for application in the petroleum and natural gas industries.

This specification follows a common document structure comprising the four documents as shown below, which together with the purchase order define the overall technical specification for procurement.



JIP33 Specification for Procurement Documents Supplementary Technical Specification

This specification is to be applied in conjunction with the supporting data sheet, quality requirements specification (QRS) and information requirements specification (IRS) as follows.

IOGP S-728: Supplementary Specification to API Standard 674 Reciprocating Positive Displacement Pumps

This specification defines the technical requirements for the supply of the equipment and is written as an overlay to API Standard 674, following the API Standard 674 to the extent applicable to the scope of supply.

Modifications to API Standard 674 defined in this specification are identified as Add (add to clause or add new clause), Replace (part of or entire clause) or Delete.

IOGP S-728D: Data Sheet for Reciprocating Positive Displacement Pumps

The data sheet defines application specific requirements, attributes and options specified by the purchaser for the supply of equipment to the technical specification. The data sheet may also include fields for supplier provided information attributes subject to purchaser's technical evaluation. Additional purchaser supplied documents may also be incorporated or referenced in the data sheet to define scope and technical requirements for enquiry and purchase of the equipment.

IOGP S-728Q: Quality Requirements for Reciprocating Positive Displacement Pumps

The QRS defines quality management system requirements and the proposed extent of purchaser conformity assessment activities for the scope of supply. Purchaser conformity assessment activities are defined through the selection of one of four generic conformity assessment system (CAS) levels on the basis of evaluation of the associated service and supply chain risks. The applicable CAS level is specified by the purchaser in the data sheet or in the purchase order.

IOGP S-728L: Information Requirements for Reciprocating Positive Displacement Pumps

The IRS defines the information requirements, including contents, format, timing and purpose to be provided by the supplier. It may also define specific conditions which invoke information requirements.

The terminology used within this specification and the supporting data sheet, QRS and IRS follows that of API Standard 674 and is in accordance with ISO/IEC Directives, Part 2 as appropriate.

The data sheet and IRS are published as editable documents for the purchaser to specify application specific requirements. The supplementary specification and QRS are fixed documents.

The order of precedence (highest authority listed first) of the documents shall be:

- a) regulatory requirements;
- b) contract documentation (e.g. purchase order);
- c) purchaser defined requirements (data sheet, QRS, IRS);
- d) this specification;
- e) API Standard 674.

2 Normative References

Add to clause

AGMA 6013, *Standard for Industrial Enclosed Gear Drives*

HI 6.1-6.5, *American National Standard for Reciprocating Power Pumps for Nomenclature, Definitions, Application, and Operation*

IEC 60079 (all parts), *Explosive atmospheres*

IOGP S-717, *Supplementary Specification to ISO 15664 Noise Emitting Equipment*

ISO 9223, *Corrosion of metals and alloys — Corrosivity of atmospheres — Classification, determination and estimation*

ISO 12944 (all parts), *Paints and varnishes — Corrosion protection of steel structures by protective paint systems*

NACE MR0175/ISO 15156, *Petroleum and natural gas industries — Materials for use in H₂S-containing environments in oil and gas production — Part 2: Cracking-resistant carbon and low-alloy steels, and the use of cast irons*

NACE MR0103/ISO 17945, *Petroleum, petrochemical and natural gas industries — Metallic materials resistant to sulfide stress cracking in corrosive petroleum refining environments*

NFPA 70, *National Electrical Code*

4 General

4.1 Units of Measurement

Replace subclause with

The technical data and its associated system of units shall be in accordance with IOGP S-728D.

4.2 Subvendor control

Replace "the International Standard" with

this specification

6 Basic Design

6.1 General

6.1.5

Replace first sentence with

If the equipment sound pressure level exceeds the specified threshold, the requirements of IOGP S-717 shall apply.

6.1.15

In first sentence, replace "(see 8.3.6)" with

(see 8.3.7)

6.5 Cylinder Connections

6.5.5

Add new list item c)

- c) if the service is non-hazardous, non-toxic, non-flammable and the corrosion rate is less than 125 $\mu\text{m}/\text{yr}$ (5 mil/yr).

6.5.14 Flanges:

6.5.14.1

Replace first sentence with

Flanges shall conform to ISO 7005-1 or B16.42.

6.5.14.2

Delete subclause 6.5.14.2

6.5.14.4

Replace "16.42" with

ASME B16.42

6.7 Liquid End Features

6.7.1 Liners

6.7.1.1

Delete "Unless otherwise specified," from subclause

6.7.2 Pistons, Plungers, and Piston Rods

6.7.2.4

Add to subclause

Hollow plungers shall have at least 3.2 mm ($1/8$ in.) wall thickness.

6.7.4 Gaskets

Replace "To prevent extrusion, and for operating pressures over 2,400 mPa" with

To prevent extrusion for operating pressures over 2,400 kPa

6.8 Power End Running Gear

6.8.3

Delete "or sufficient wall thickness for re-boring" from second sentence

6.8.5

In second sentence, replace "AGMA 6010" with

AGMA 6013

In third sentence, replace "AGMA 6010" with

AGMA 6013

6.9 Direct-Acting Pump

Add new subclause

6.9.8

Direct-acting pump drives shall have a minimum DN 15 (NPS ½) drain connection that evacuates the cylinder.

6.11 Materials

6.11.2 General

6.11.2.1

Add to subclause

When cast iron is acceptable for the service, it shall be nodular cast iron.

6.11.2.11

In second sentence of first paragraph, replace "MR0 175" with

NACE MR0175/ISO 15156 and/or NACE MR0103/ ISO 17945

In third sentence of first paragraph, replace "NACE Standard MR0 175" with

NACE MR0175/ISO 15156 and/or NACE MR0103/ ISO 17945

In first sentence of subclause a), replace "MR0175" with

NACE MR0175/ISO 15156 and/or NACE MR0103/ ISO 17945

6.12 Nameplates and Rotation Arrows

6.12.2

Delete "if direction of rotation affects performance and/or reliability" from subclause

6.12.4

Add new list item m)

m) year of manufacture.

7 Accessories

7.1 Drivers

7.1.4 Gear Units

7.1.4.2

Replace first sentence with

Coupled gears shall be single helical or double helical type conforming to AGMA 6013.

7.1.4.3

In last sentence, replace "AGMA 6010" with

AGMA 6013

7.5 Controls and Instrumentation

7.5.4 Instrumentation

Add new subclause

7.5.4.5 Instrument Certification

Calibration certificates shall be provided for all instrumentation installed on the equipment.

Add new subclause

7.6 Auxiliary Piping

7.6.4

For services that are hazardous, toxic or flammable, the drain and vent piping connections shall be piped to the skid edge.

Add new subclause

7.6.5

All auxiliary piping connections shall be piped to the skid edge.

7.7 Pulsation and Vibration Control Requirements

7.7.1 General

7.7.1.2

Replace second and third sentence of subclause a) with

Pulsation control devices shall be supplied by the Vendor.

8 Inspection, Testing, and Preparation for Shipment

8.1 General

8.1.1

Replace subclause with

Inspection, testing and certification shall be carried out in accordance with IOGP S-728D and IOGP S-728Q.

8.3 Testing

8.3.1 General

8.3.1.1

Replace subclause with

Equipment shall be tested in accordance with 8.3.2, 8.3.3, 8.3.4 and either 8.3.5 or 8.3.6 as appropriate.

8.3.2 Hydrostatic Testing

8.3.2.2

Replace "SECTION VII" with

SECTION VIII

8.3.4 Mechanical Run Test

8.3.4.7

Delete subclause 8.3.4.7

8.4 Preparation for Shipment

8.4.3

8.4.3.1

Add to subclause

Painting shall conform to the requirements of ISO 12944.

Add to subclause

A high durability paint system shall be applied.

Registered Office

City Tower
Level 14
40 Basinghall Street
London EC2V 5DE
United Kingdom
T +44 (0)20 3763 9700
reception@iogp.org

Brussels Office

Avenue de Tervuren 188A
B-1150 Brussels
Belgium
T +32 (0)2 790 7762
reception-europe@iogp.org

Houston Office

15377 Memorial Drive
Suite 250
Houston, TX 77079
USA
T +1 (713) 261 0411
reception-americas@iogp.org

| www.iogp.org

